



Features

- For service, display shows all messages
- Backlit display
- User-friendly Menu
- Common Control buttons with selector switches and LEDs
- Four Status Queues: Alarm, Supervisory, Trouble and Monitor
- Mounted in backboxes, BBX-1072ADS(ARDS), BB5008(R), BB-5014 and the BBX-FXMNS Backbox

Description

The DSPL-2440 Graphical Main Display Module provides the FX-MNS with a 24-line x 40-character backlit LCD display, common controls buttons and four status queues with selector switches and LEDs for Alarm, Supervisory, Trouble and Monitor. The DSPL-2440 occupies one display position in the FX-MNS enclosure.

The DSPL-2440 may be used for service; this display will show all messages.

Power Consumption

Normal Operation Voltage	Amps
Stand by	29 mA
Alarm	35 mA

Ordering Information

Model	Description
DSPL-2440	Graphic Display for FX-2000MNS



Canada
 25 Interchange Way Vaughan, ON L4K 5W3
 Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.
 4575 Witmer Industrial Estates Niagara Falls, NY 14305
 Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.

CATALOG NUMBER **5333**

Rev. 0