



Features

- For service, display shows all messages
- Backlit display
- User-friendly Menu
- Common Control buttons with selector switches and LEDs
- Four Status Queues: Alarm, Supervisory, Trouble and Monitor
- Mounted in backboxes, UB-1024DS, BBX-1024XT(B)R, BBX-1072ADS(ARDS), BB5008, BB-5014 and the BBX-FXMNS(R) Backbox

Description

The DSPL-2440DS Graphical Main Display Module provides the Flex-Net Series with a 24-line x 40-character backlit LCD display, common controls buttons and four status queues with selector switches and LEDs for Alarm, Supervisory, Trouble and Monitor. The DSPL-2440DS occupies one display position in the inner door of the Flex-Net Series.

The DSPL-2440DS may be used for service; this display will show all messages.

Voltage	24 VDC
----------------	--------

Current Consumption

Stand by	29 mA
Alarm	75 mA

Ordering Information

Model	Description
DSPL-2440DS	FLEX-NET 24-Line x 40-Character Graphical Main Display Module



Canada

25 Interchange Way Vaughan, ON L4K 5W3
Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.

4575 Witmer Industrial Estates Niagara Falls, NY 14305
Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.

CATALOG NUMBER 5343

Rev. 1