

### INTELLIGENT SOUNDER BASE



# Description

The System Sensor B200SR series sounder bases set a new standard for performance, installation ease, and aesthetics. The B200SR sounder base is designed for new and existing dwelling unit applications. It offers maximum flexibility in installation, configuration, and operation to meet or exceed UL 268, UL 464, CAN/ULC S529 and CAN/ULC S525 requirements.

The B200SR is fully compatible with existing B501BH-Series sounder base installations. The device enables users to select one of two B501-supported tones (ANSI Temporal 3 or Continuous) by removing a jumper.

With its attractive aesthetics, the B200SR is ideal for applications where appearance is critical. For example, the sounder base employs a separate mounting plate that installs on various junction box sizes to eliminate unsightly surface-mount boxes. In addition, the mounting plate enables pre-wiring of all connections to speed and simplify installation. The housing then mates with the mounting plate and is locked in position with two retaining screws, which are covered by the installed sensor head for added tamper resistance.

#### **Features**

- Tone selection via an onboard jumper
- UL 268 and UL 464 compliant
- ULC listed as smoke detector base and audible signal appliance
- Pre-wire mounting plate fits various junction box sizes
- Fully compatible with existing B501BH-Series sounder base installations
- Mechanical locking feature prevents removal of attached sensor head









## **Specifications**

Physical Specifications	
Base Diameter	6.875" (17.46 cm)
Base Height	2.0" (5.08 cm) less sensor
Shipping Weight	0.50 lb. (227 gm)
Operating Temperature Range	32° to 120° F (0° to 49° C)
Operating Humidity Range	10% to 93% relative humidity (non-condensing)
Electrical Specifications	
External Supply Voltage	16 to 33 VDC (VFWR)
External Supply Standby Current	500 μA maximum
Alarm Current	35 mA maximum
SLC Operating Voltage	15 to 32 VDC
SLC Standby Current	300 μA maximum
Sound Output	Greater than 85 dBA minimum – measured in a UL reverberant room at 10 ft. 24 Volts (in continuous tone)

## **Ordering Information**

Model	Description
B200SR	Intelligent Sounder Base
B200SRA	Intelligent Sounder Base (Canadian model)

#### NOT TO BE USED FOR INSTALLATION PURPOSES.



25 Interchange Way Vaughan, Ontario L4K 5W3 Telephone: (905) 660-4655 Fax: (905) 660-4113

Web page: http://www.mircom.com

U.S.A. 4575 Witmer Industrial Estates Niagara Falls, NY 14305 Toll Free: (888) 660-4655 Fax Toll Free: (888) 660-4113

Email: mail@mircom.com



