



FDX-008W



FDX-008W/KI

Description

There are two models of the Fan Damper Control Display modules available.

The FDX-008W Fan Damper Module provides configurable output circuits for Fan Damper and Purge control and has 8 switches.

The FDX-008W/KI provides 7 switches and a terminal block is used to connect a key switch to enable the fan/purge control function.

The FDG-008 Fan Damper Graphics Control Module provides the same control (eight switches and associated LED indicators) as the FDX-008W except through a graphics display.

Each circuit has a slide in label and a three-position selector switch with Green "ON" or (open) LED, Amber "OFF" and a Yellow "TROUBLE LED. The three-position selector switch has a centre Auto position with White LED system running, a left "OFF" (or closed) position and a right "ON" (or open) position.

In the "Auto" position the fan or damper follows the fire alarm programming when an alarm occurs. When the switch is turned to the "OFF" position the fan or damper is turned off or closed.

If the fan or damper is normally on or open, it will turn off or close when the switch is moved to the "OFF" position.

Features

- FDX-008W provides switch control and LED indication of 8 fan damper zones.
- FDX-008W/KI provides switch control of 7 fan damper zones with terminals for a keyswitch
- FDG-008 board is used as a graphic driver for smoke control and takes up two module spaces in the backbox enclosure/s.
- Compatible with FleX-Net & FX-2000 Fire Alarm Control Panels
- Tested and approved under the following standards UL 864, NFPA 72, 101, 90A, 92A, 92B, (Smoke Control Category)

Benefits

- Provides automatic control of fans and/or dampers (based upon smoke detector input)
- LEDs can be set up to monitor the progress of the smoke in the same manner as on a standard fire alarm display

When the switch is moved to the "ON" position the fan or damper is turned on or open. If the fan or damper is normally off or closed, it will turn on or open when the switch is moved to the "ON" position.

The FDX-008W/KI can be connected to the main display or it can be connected to the RAX-LCD, RAXN-LCD or RAXN-LCDG Remote Shared Display.

The FDX-008W/KI takes up one frame when connected to the main or remote share display and occupies one position in the BB-1000, BB-5000, BBX-1000, and BBX-FXMS enclosures.



NYC
Fire Dept.

Specifications

FDX-008W & FDX-008WKI Display Module

- 24V DC nominal, range of 20 to 39V DC
- Interconnects via one ribbon cable to P2 of previous display module
- Provides 8 configurable output circuits or fan damper controls
- Standby: 15mA Max., Alarm (all LEDs ON): 35mA Max

FDG-008 Fan Damper Graphic Control Module

- 5V DC internally provided by the FX-2000, FleX-Net Fire Alarm Control Panels
- Interconnects via one ribbon cable to P2 of previous display module
- Provides 8 configurable output circuits or fan damper controls
- Standby: 15mA Max., Alarm (all LEDs ON): 35mA Max

***NOTE:** Use the FX-2000, FleX-Net Fire Alarm Control Panel Manual in conjunction with this document for complete installation information

Ordering Information

Model	Description
FDX-008W	Fan Damper Control Display Module (8 SWITCH)
FDX-008WKI	Fan Damper Control Display Module (7 SWITCH & KEY)
FDG-008	Fan Damper Graphic Control Module



Canada
25 Interchange Way
Vaughan, Ontario L4K 5W3
Telephone: (905) 660-4655
Fax: (905) 660-4113

U.S.A.
4575 Witmer Industrial Estates
Niagara Falls, NY 14305
Toll Free: (888) 660-4655
Fax Toll Free: (888) 660-4113



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.