



Features

- Conformal Coated Annunciator
- Sealed membrane-like buttons and LED indicators
- Local Buzzer, Indicators (AC-On, Common Trouble, Remote Failure, Aux. Disconnect, Acknowledge, General Alarm, Signal Silence, Test/Config Mode), and Controls (System Reset, Lamp Test, Fire Drill, Aux. Disconnect, Buzzer Silence, Signal Silence, General Alarm, Acknowledge)
- Buzzer silence activation silences the main fire alarm panel buzzer and all attached annunciator buzzers
- Annunciation of up to 32 points with trouble annunciation.
- Expandable by using up to four RAX modules

Description

The RAM-1032TZDS-CC Main Remote LED Annunciator provides common annunciator functions and 32 points of LED annunciation. The RAM-1032TZDS-CC has indicators for A.C. On, Common Trouble and Signal Silence and controls for System Reset, Lamp Test, Fire Drill, Buzzer Silence and Signal Silence.

Each display point can be identified by the slide-in label that slides in besides the LED. The RAM-1032TZDS-CC allows for the control switches to be disabled on a per function basis for areas that do not require certain common control functions to be remotely located from the fire alarm control unit. The RAM-1032TZDS-CC can be expanded with the addition of RAX-1048TZDS-CC Programmable LED Annunciator Modules.

Both RAM-1032TZDS-CC and RAX-1048TZDS-CC are conformal coated annunciators and are UL and ULC approved for outdoor use when used with BB-1001WPRA or BB-1002WPRA. No heat or thermostat is needed.

Power Consumption

Normal Operating Voltage	20 to 39 VDC
Stand by	50 mA
All LEDs "On"	300mA

Ordering Information

Model	Description
RAM-1032TZDS-CC	32 Zone Conformal Coated Remote LED Annunciator
Expandable RAX Conformal Coated option	
RAX-1048TZDS-CC	48 Zone Conformal Coated Remote LED Annunciator



Canada

25 Interchange Way Vaughan, ON L4K 5W3
Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.

4575 Witmer Industrial Estates Niagara Falls, NY 14305
Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.