



### Features

- 2 line x 20 character LCD back-lit display (Non-scrolling directory)
- DIP switch selectable for either AutoDialer or NSL (No Subscriber Line) systems
- Field programmable via the keypad
- Multiple entrance capabilities
- Flexible one to four digit resident codes
- Keyless Entry Codes
- Tone or Pulse compatible
- User Event Tracking for visitors and keyless entry
- Connection for "Lock Back" door contact to prevent "tailgating"
- Built-in Real Time Clock (Y2K Compliant)
- Elevator restriction capability
- RS-485 Interface to network to other units
- Postal lock provision
- Option for the Mircom CAM-1 Camera
- Exclusive Distinct Suite Telephone Ring Pattern (NSL only)
- Industry Canada and F.C.C. approved

### Description

Mircom's MUS-1360K Slim Line Lobby Panel is designed to provide Resident/Visitor access control for buildings such as apartments, multi-dwellings, condominiums and offices for up to 360 residents.

The MUS-1360K Slim Line Lobby Panel is constructed of a heavy gauge stainless steel designed for surface mounting. The system comes complete with a 2 x 20 character non-scrolling back-lit LCD display which provides clear messages. In addition it has provisions for both a postal lock switch and a camera. The unit can be semi-flush mounted using the optional USFT-1000 semi-flush trim ring. For extremely cold climates, the TH-102 Heater Kit is recommended with this panel.

The MUS-1360K Slim Line Lobby Panel is dip switch selectable for either the AutoDialer system, which uses a dedicated phone line to dial preprogrammed telephone numbers when the unique directory code is entered, or the No Subscriber Line system, which does not require a dedicated phone line. The AutoDialer systems require a dedicated phone line while the NSL systems require other hardware components such as relay cards and relay cabinets. (Please refer to the ordering information.) The system is programmable via its integrated metal keypad or using a computer with the optional MirSoft TAS software and MDM-1000 Modem Module.

The MUS-1360K Slim Line Lobby Panel provides telephone access control at an affordable price. Typical features considered optional on other competitive systems are standard with this Slim Line Lobby Panel. Features such as Exclusive Distinct Suite Telephone Ring Pattern which enables management or a service technician to change the ring pattern of a suite which has smart telephone devices that do not pass conventional intercom ring patterns, to conventional telephone ring patterns, without affecting the remainder of the suites in the building. (Available only on NSL systems.)

The MUS-1360K also comes with a User Event Tracking capability which logs the activity of both visitors as well as resident keyless entry. The Event log can be reviewed via keypad or a computer with the optional MirSoft TAS software and MDM-1000 Modem Module.

Installers will find installation is easy and fast, while the end user will find the system easy to operate. Equipped with illuminated directories, the MUS-1360K Slim Line Lobby Panel is viable in any environment.

## Operation

The MUS-1360K allows for duplex communications by permitting a visitor to enter a resident code at the entrance panel which causes the resident's phone to announce that a visitor is present. The resident can use their own phone to establish communication with the visitor.

If the resident desires the visitor to enter, they can dial "9" which causes the entrance door to open for a predetermined time. If entry is not desired, then access can be refused by simply hanging up.

## Dimensions

### MUS-1360K

15.62" H x 5.85"W x 4.5"D

### USFT-1000

18.75"H x 8.94"W

## Ordering Information

### MODEL NO.

### DESCRIPTION

#### Lobby Panels

MUS-1360K

Self contained, Hands free unit c/w 2 x 20 character non-scrolling directory LCD Display, 360 name capability, metal keypad, back box and one PS-4 transformer (Canada)/PS-4P transformer (U.S.A.)

#### NSL Components

2008M

Master NSL Relay Cabinet. Supports eight 2012 Telephone Line Relay Cards  
Includes two PS-24 (Canada)/PS-24P (USA) Transformers.

2008

8 Relay Card Expander Cabinet

2016

16 Relay Card Expander Cabinet

2012

12 Unit Telephone Line Relay Card

9106

6 ft. Relay Cable (one required per 2012 Telephone Line Relay Card)

9106BC

6 ft. Relay Cable for B.C.

2008E

Elevator Restriction Relay Cabinet. Supports eight 2012E Elevator Restriction Relay Cards. Includes one PS-24 (Canada)/PS-24P (USA) Transformer.

2012E

12 Unit Elevator Restriction Relay Cards

#### Accessories

TH-102

Thermostat Heater kit for Slim Line Lobby Panels.  
Requires separate 24 VAC power source (PS-3B/PS-3P)

USFT-1000

Semi-flush trim ring

CAM-1

Board Camera c/w power supply

PS-24

Transformer 24 VAC/40VA (PS-24P for USA version)

PS-3B

Transformer 8VAC/13VA, 16VAC/17VA, 24VAC/20VA (PS-3P for USA version)

PS-4

Transformer 16VAC/40 VA (PS-4P for USA version)

MDM-1000

Modem Module

M-10

Door Strike 8-12 VAC

MSW-003

MirSoft TAS 2000

RS-485IMA

Interface Module

NOT TO BE USED FOR INSTALLATION PURPOSES.



#### Canada

25 Interchange Way  
Vaughan, Ontario L4K 5W3  
Telephone: (905) 660-4655  
Fax: (905) 660-4113

#### U.S.A.

4575 Witmer Industrial Estates  
Niagara Falls, NY 14305  
Toll Free: (888) 660-4655  
Fax Toll Free: (888) 660-4113

Distributed by:

Web page: <http://www.mircom.com> Email: [mail@mircom.com](mailto:mail@mircom.com)



CAT. 6520  
Rev. 4