



## Description

The AT1-Gard single door keypad brings strength and reliability to a price sensitive market. The AT1-Gard is offered in a 3 x 4 surface mount design and includes tamper proof mounting with the supplied hardware.

All metal construction with anodized graphics guarantee that the AT1-Gard will survive in the most harshest environments.

The AT1-Gard is a single door solution utilizing a multi-function Piezo keypad capable of storing up to 200 User Codes, as well as a Master Code for administration.

The AT1-Gard can be utilized in a wide range of environments. This includes labs, health clubs, public pools, condo and townhouse shared areas, garage doors, parking and secure gate areas, marine and dock areas, as well as any location that needs a secure and rugged keypad for high traffic areas.

## Features

- 200 PIN users
- Smooth attractive design, with anti-vandal/anti-weather casing
- One piece, solid metal design with no moving parts
- Highly-sensitive Piezoelectric metal keys
- Multiple user levels: Normal, Master, and Programming
- Supports up to 8-digit PIN codes
- Code search feature for easy maintenance of user codes
- Single tri-colored LED and integral sounder for programming and operation
- Supplied with mounting template for easy installation

## Professional Grade Features

- Internal buzzer
- Vandal proof mounting
- Auxiliary input and output (2 Amp Form C Relay)
- 2 Amp Form C Lock Strike Relay for fail-safe and fail-secure
- Programmable lock strike release time
- Wide range of low voltage AC/DC power input (12-24V AC/DC)
- Low power consumption 150mA max.
- Meets IP69 for outdoor use-weather/vandal proof design

## Specifications

<b>Material</b>	One-piece aluminum, brushed natural finish, anodized graphics
<b>Electrical</b>	IP69, weather/water proof, -40°C - 125°C operating temperature
<b>Power</b>	12-24V AC/DC, 150mA Max., 2A Form C Relay
<b>User Codes</b>	200, 4-8 digit codes, 100 million combinations
<b>Programming</b>	1 Master code, set door opening time, set remote door opening time, output to latch mode, set user codes
<b>Wiring</b>	Brown (+ 12-24V), Blue (Ground), Black (Common), Red (NO-2A Form C relay), Yellow (NC), White/Orange (Remote Open Door Switch)
<b>Dimensions</b>	3.125" W, 5.125" L, .500" H

## Ordering Information

Model	Description
39201170	AT1-Gard Standalone Single Door Keypad

NOT TO BE USED FOR INSTALLATION PURPOSES.



**Canada**  
25 Interchange Way  
Vaughan, Ontario L4K 5W3  
Telephone: (905) 660-4655  
Fax: (905) 660-4113

**U.S.A.**  
4575 Witmer Industrial Estates  
Niagara Falls, NY 14305  
Toll Free: (888) 660-4655  
Fax Toll Free: (888) 660-4113

Web page: <http://www.mircom.com> Email: [mail@mircom.com](mailto:mail@mircom.com)

Distributed by:

ISO 9001:2008  
REGISTERED



CAT. 6538  
Rev. 0