

**TX3 Series**


CSR-6.2  
Mounts to mullion



CSR-6.4  
Mounts to single-gang wall switch box



Doors



Parking



Turnstiles

**Description**

Mircom's TX3-CSR-6.2 and TX3-CSR-6.4 comprises contactless smartcard reader solution with mobile access support. Based upon the proven LEGIC® contactless digital radio frequency identification (RFID) platform. Our readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand and ABA Track II magnetic stripe formats. They offer value-add features such as MAXSecure™ and ValidID™, and support both sector and card serial number (CSN) reads. In addition to traditional contactless smartcard access credentials, such as clamshell cards and key tags, the platform also offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE)-enabled smartphones. This allows the smartphone to function as a contactless electronic access control credential. Mircom's access credentials, both traditional and mobile, can be ordered programmed to various formats in exact number sequence required.

**Features**

- **Bluetooth Low Energy**  
Supports Conekt Smartphone Mobile Access Credentials
- **Optimized for MIFARE® DESFire® EV1 & EV2**  
Integrated High-Security Contactless Smartcard Support
- **MAXSecure™**  
Unique Security Feature
- **ValidID™**  
Fraudulent Data Detection Solution
- **Wiegand, ABA Track II Magnetic Stripe**  
Output Interface
- **Mullion Mount (TX3-CSR-6.2)**  
Metal Door, Window Frames & Flat Surfaces
- **U.S. Single-Gang Wall-Box Mount (TX3-CSR-6.4)**  
Box & Flat Surfaces

## Specifications

Models	TX3-CSR-6.2 Mullion-Mount Mobile-Ready Contactless Smartcard Reader and Keypad TX3-CSR-6.4 Single-Gang Wall Switch Box Mount Mobile-Ready Contactless Smartcard Reader and Keypad
Technology <sup>1</sup>	Contactless smartcard and Bluetooth Low Energy (BLE)
Frequency	13.56 MHz (contactless smartcard) and 2.4 GHz (BLE)
Mounting <sup>2</sup>	TX3-CSR-6.2: Mullions, including metal door and window frames, as well as flat surfaces TX3-CSR-6.4: Single-gang wall box, as well as flat surfaces
Dimensions	TX3-CSR-6.2: 1.78" W × 6.1" H × 0.91" D (45 mm × 155 mm × 23 mm) TX3-CSR-6.4: 3" W × 4.6" H × 0.75" D (76 mm × 117 mm × 19 mm)
OEM Label Area	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.06" (1.5 mm)
Certifications	FCC, ICC, CE
IP Code	IP67
Voltage <sup>3</sup>	+8 – 14 VDC
Current Draw	175 mA typical @ 12 VDC
Read Range <sup>4</sup>	Physical Credentials: Up to 2 inches (51 mm) Mobile Credentials: Up to 15 feet (4.6 m)
Cabling <sup>5</sup>	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand (26-bit and custom formats), ABA Track II magnetic stripe (clock and data)
Operating Temperature	–40° F to 149° F (–40° C to +65° C)
Color Options	A black snap-on cover included standard
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
Keypad Output	Either Wiegand <sup>6</sup>
Technologies Supported	Interoperable with CSN <sup>7</sup> (may include ISO 14443 compliant credentials and MIFARE® Classic 1k & 4k, MIFARE® DESFire® EV1 & EV2, MIFARE UltraLight® and MIFARE Plus®), and Sector (may include Delta Card Sector <sup>8</sup> , such as MIFARE® Classic 1k & 4k, MIFARE® DESFire® EV1 & EV2, as well as FIPS201 [PIV Type A], TWIC, and CAC credentials), as well as Conekt Mobile Access Credentials. <sup>9</sup>

### NOTES:

- 1 Optimized for use with devices supporting BLE version 4.2 or newer.
- 2 Spacer included standard for installations on metal. Depending on environment, additional spacing may be required.
- 3 Linear power supplies are recommended for best operation.
- 4 Using DC1-1 Delta Clamshell Contactless Smartcard with 12 VDC at the reader. Other credentials may be less. Read ranges are further subject to the type of smartphone, as well as the manner in which it is used, covers or external batteries affixed, as well as the installation and its environment.
- 5 For example, Belden 9535 or similar, supporting the five conductors comprising the physical layer of the Wiegand interface (power, ground, data 0, data 1, and/or beeper and LED). Alternatively, Belden 9539 or similar, for all reader functions.
- 6 8-Bit Burst or 26-bit Wiegand standard. For 4-Bit Burst and other options, please contact Farpointe.
- 7 CSN = Card Serial Number.
- 8 Examples include, but are not limited to, DC1-1, DM1-3, and DK1-3.
- 9 Conekt Mobile Access Credentials are intended to be supported by the current and preceding versions of Apple® iOS and standard compliant Google Android™ mobile operating software (OS). Custom OS variants may result in a loss of functionality.

Patent Pending

© 2020 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. LEGIC is a registered trademark of LEGIC Identsystems Ltd. MIFARE, MIFARE DESFire, MIFARE UltraLight, and MIFARE Plus are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

## Ordering Information

Model	Description
TX3-CSR-6.2	Mullion-Mount Mobile-Ready Contactless Smartcard Reader and Keypad
TX3-CSR-6.4	Single-Gang Wall Switch Box Mount Mobile-Ready Contactless Smartcard Reader and Keypad



**Canada**  
25 Interchange Way  
Vaughan, Ontario L4K 5W3  
Telephone: (905) 660-4655  
Fax: (905) 660-4113

**U.S.A.**  
4575 Witmer Industrial Estates  
Niagara Falls, NY 14305  
Toll Free: (888) 660-4655  
Fax Toll Free: (888) 660-4113



This document is provided by Mircom Technologies Ltd., MGC Systems Corp., or their affiliates, subsidiaries and brands, for convenience or marketing only and does not describe products or services technically. For technical information refer to technical manuals. We do not make representations or warranties regarding this information, including as to completeness or accuracy. We may change these contents at any time and reserve all rights in the contents, including copyrights, trademarks and other intellectual property.