

**TX3
Series**
VOICE ENTRY


Description

Mircom's TX3 Reinforced Slim Line Voice Access Systems are designed to provide visitor access control to doorways, Overhead doors, or barrier gates for up to 2000 occupants. The slim line space-efficient design is ideal for application with limited space, for application where a separate directory is exists or not require.

The TX3 Reinforced Universal Series enclosure is constructed from robust, heavy gauge stainless steel and it is suitable for both indoor lobby and outdoor installation. This system offers versatile mounting options, including surface, semi-flush, or pedestal mounting. The Reinforced Universal Series enclosure offers features such as a built-in rain hood, microphone, tamper-resistant speaker, and has provisions for the installation of a postal lock and color camera.

The TX3 Reinforced Slim Line system features a back-lit 4 line by 20 character electronic LCD display that scrolls a programmable banner message as well as the resident names and dial codes. The system also features a 16 digit backlit telephone style keypad with dedicated operational buttons for Page Up, Page Down, Call and Info.

The systems are programmable either via its built-in keypad or through a computer with the optional TX3 configuration software. In addition, remote configuration is a seamless option via the TX3 configuration software and TX3-MDM Modem Module.

Features

- TCP/IP capability for remote programming by adding a TX3-IP module
- Stainless steel front panel for enhanced durability.
- Reinforced Universal Series slim line enclosure with built-in rain hood
- Scrolling 4 x 20 backlit LCD display that eliminates the need for an external directory
- Extensive User Capacity; Supports up to 2000 names
- Backlit 16 digit keypad with dedicated operational buttons for Page Up, Page Down, Call and Info
- Provision for postal lock or card reader (TX3-P300-HA card reader sold separately)
- Provision to add optional TX3-WIEGAND-OUT module to integrate any Wiegand compatible 3rd party access control system with Mircom's TX3 Voice Entry systems
- Field-Configurable Multilingual Display and Voice Greeting (English, French-Canadian, and Spanish) for user instructions.
- Concierge/Security Desk/Guard Phone capability
- Supports both AutoDialer (ADC) and NSL (No phone bill)
- Ability to network panels together (peer-to-peer)
- Dials up to 18 digit telephone numbers
- System can be configured locally using the keypad or a computer with the TX3 configuration software
- Remote programming requires a computer equipped with a USB modem and a TX3-MDM modem module installed in the lobby unit
- Upload/download configuration files without system downtime.
- Programmable daily usage postal lock
- Record 5000 events in the event log
- Provision for a covert color camera; CAM-3

Applications

- Provides robust resident/visitor access control solutions for small-scale structures, such as condominiums, apartment buildings, office complexes, gated communities, and industrial facilities.
- Surface, semi-flush or pedestal mounting options (Optional adapter plate required to mount to a standard gooseneck post)
- The TX3 system utilizes a hands-free, full-duplex telephone communication between residents and visitors for streamlined access to the building. The system can be configured to support AutoDialer (ADC) and No Phone Bill (NSL) modes. ADC system Utilizes a dedicated phone line to dial preprogrammed numbers when the unique directory code is entered. while NSL system operates without the need for a dedicated phone line.

Dimensions

Model	Dimensions
TX3-2000-4UR-C	16 7/8" H x 5 7/8" W x 4 1/2" D (428 mm x 149 mm x 114 mm)
TX3-USFTR Semi-Flush Trim Ring	Overall dimensions: 19 5/8" H x 8 7/8" W x 2 1/16" D (498 mm x 225 mm x 53 mm) Wall cutout dimensions: 17 1/2" H x 6 1/2" W x 2" D (445 mm x 165 mm x 51 mm)

Ordering Information

Model	Description
TX3-2000-4UR-C	Reinforced Universal enclosure c/w 4x20 LCD display, 2000 name controller and (1) PS-4P transformer.
Slim Line Mounting Accessories	
TX3-USFTR	Semi-Flush mounting trim kit designed for use with the Reinforced Slim Line Universal Series enclosures
TX3-USGA	Gooseneck mounting adapter designed for use with the Reinforced Slim Line Universal Series enclosures
No Phone Bill (NSL) Components	
TX3-NSL-8M	Master NSL Relay Cabinet. Supports eight 2012 Telephone Line Relay Cards.
TX3-8EC	8 Relay Card Expander Cabinet
TX3-16EC	16 Relay Card Expander Cabinet
9106	6 ft. relay cable for 2012
2012K	NSL Relay Card and Cable Kit. Kit includes (1) 2012 twelve unit telephone relay card and (1) 9106 six ft. relay cable
ADSL-100	ADSL line filter module for NSL applications
Elevator Restriction Components	
TX3-ER-8-B	Master Elevator Restriction Cabinet with IP capability. Order TX3-IP Module for TCP/IP
3012E	Twelve Unit Elevator Restriction Relay Card
Optional Modules	
TX3-WIEGAND-OUT	TX3 Voice Entry Wiegand Output. Supports integration with 3rd party Access Control systems.
TX3-IP	Add on TCP/IP module
TX3-MDM	Modem Module
TX3-GPM	Guard Phone Module
TX3-MSW	TX3 Configuration Software
CAM-3	Color Camera
TX3-P300-HA	Mullion mount card reader. Fits inside panel
TH-102	Heater Kit. Requires PS-24.
PS-24	24VAC Transformer



Canada

25 Interchange Way Vaughan, ON L4K 5W3
Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.

4575 Witmer Industrial Estates Niagara Falls, NY 14305
Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com



This document is provided by Mircom Technologies Ltd., MGC Systems Corp., or their affiliates, subsidiaries and brands, for convenience or marketing only and does not describe products or services technically. For technical information refer to technical manuals. We do not make representations or warranties regarding this information, including as to completeness or accuracy. We may change these contents at any time and reserve all rights in the contents, including copyrights, trademarks and other intellectual property.

CAT. 6588

Rev. 0