

Specifications

Voltage Range
15 to 32 VDC
Standby Current
300 uA @ 24 VDC (one communication every 5 sec. with LED blink enabled)
LED Current (max.)
6.5 mA @ 24 VDC (on)
Height
2.0 inches (51 mm) installed in B210LP Base
Diameter
6.1 inches (155 mm) installed in B210LP Base 4.1 inches (104 mm) installed in B501 Base

Shipping Weight
5.2 oz. (147 g)
Operating Humidity Range
10% - 93% non-condensing
Operating Temperature Range
MIX-2251RAP: 32°F to 120°F (0°C to 49°C) Duct Applications: -4°F to 158°F (-20°C to 70°C)
UL Listed Velocity Range
LUHORFLW:0 - 4000 fpm

Ordering Information

e	e
MIX-2251RAP	Intelligent Photoelectric Smoke Sensor with Remote Test Capability for Duct Applications
B501	Intelligent Flangeless Mounting Base
B210LP	Intelligent Flanged Mounting Base
RA-100Z	Remote LED Annunciator

Add suffix "A" for ULC listed model.



Canada
25 Interchange Way
Vaughan, Ontario L4K 5W3
Telephone: (905) 660-4655
Fax: (905) 660-4113

U.S.A.
4575 Witmer Industrial Estates
Niagara Falls, NY 14305
Toll Free: (888) 660-4655
Fax Toll Free: (888) 660-4113



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.