



MIX-4030 / MIX-4030-ISO

Description

The MIX-4030/MIX-4030-ISO detector is a hardwired sensor that continuously monitors the environmental temperature to report high heat conditions and communicates with the panel using a fully digital protocol.

An alarm will be reported when the sampled temperature exceeds 135°F (57°C) or 175°F (79°C) depending on the chosen mode of operation. Excessive temperature rises can also be reported if the detector is configured for rate-of-rise operation.

The MIX-4030/MIX-4030-ISO works with an MGC compatible control panel supporting high rates of information exchange with reliable and secure bi-directional communication.

The detector is addressed and programmed using the MIX-4090 hand-held device. Addresses can be selected from a range of 1-240.

This detector ships with a dust cover to protect the device during installation and prior to commissioning.

Two tri-color LEDs on the device provide 360 degrees of status visibility.

A remote LED indicator can be wired directly to the sensor.

Features

- Any combination of MIX-4000 series devices up to 240 can be connected on a single SLC.
- Different LED colors for Alarms and Troubles
- Three operational modes of heat detection.
- Compatible with the full series of MIX-4000 input and control modules.
- The device can be secured by a unique Anti-Tamper feature.
- The address is set with the hand-held device programmer (MIX-4090)
- MODEL OPTION - Built-in short-circuit isolator (MIX-4030-ISO)
- Operating Modes
 - Rate of rise heat detection (135°F/57°C)
 - Fixed heat detection (135°F/57°C)
 - Fixed heat detection (175°F/79°C)

Benefits

- Open style mounting bases offer easy wiring and low pressure locking
- 4" or 6" base options available
- Remote output can be controlled by the panel
- MIX-4030-ISO is equipped with a bi-directional short-circuit isolator to protect against wiring faults and loop failure.
- Low standby current.
- Base has detachable tab for labeling device address.
- Leverages interrupts to quickly report alarm conditions to fire alarm control panels.
- Magnet test option helps with commissioning and maintenance.



APPROVED

Technical Specifications

Normal Operating Voltage	15 to 30VDC
Maximum Alarm Current	3.2mA (LED on)
Standby Current	160µA
UL/ULC Listed Temperature Range	32°F to 100°F (0°C to 37.8°C)
Operating Temperature	15°F to 120°F (-9°C to 49°C)
Humidity	10% to 93% Non-condensing
Wiring range on terminals	22 to 12 AWG
Diameter	4.25"
Height	1.75"

Detector LED colors	Description
RED (Steady on)	ALARM condition
GREEN (Flash)	NORMAL condition
AMBER (Steady on)	FAULT condition
Heat Detection Settings	
135°F (57°C)	
175°F (79°C)	
135°F (57°C) rate of rise	

Ordering Information

Model	Description
MIX-4010	Photoelectric Smoke Detector (Non-Isolated)
MIX-4010-ISO	Photoelectric Smoke Detector (with short-circuit isolator)
MIX-4020	Multi-Criteria/Multi-Sensor (Non-Isolated)
MIX-4020-ISO	Multi-Criteria/Multi-Sensor (with built-in short circuit isolator)
MIX-4030	Heat Detector (Non-Isolated)
MIX-4030-ISO	Heat Detector (with built-in short circuit isolator)
MIX-4090	MIX-4000 Addressable Device Programmer
MIX-4001	6" Detector Base
MIX-4002	4" Detector Base



Canada
 25 Interchange Way
 Vaughan, Ontario L4K 5W3
 Telephone: (905) 660-4655
 Fax: (905) 660-4113

U.S.A.
 4575 Witmer Industrial Estates
 Niagara Falls, NY 14305
 Toll Free: (888) 660-4655
 Fax Toll Free: (888) 660-4113



Intertek

THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.