



MIX-4001 / MIX-4002

Description

The MIX-4001 and MIX-4002 mounting bases are used to interface series 4000 detectors to the SLC line and remote devices.

The low profile base can be wired and secured to a back-box during building construction, allowing the detector to be installed later, when premises become free of dust and other contaminants.

Features

- Sleek low profile design
- Ceiling or wall mountable
- 4" or 6" options
- The base provides a device Anti-Tamper feature

Benefits

- Open style mounting bases offer easy wiring and low pressure docking
- Save time with multiple mounting options
- A breakable flat tab in the centre of the base can be cut and inserted in the base outer edge, then a label can be used to identify the device

Technical Specifications

Wiring Range on all terminals	22 to 12 AWG
Diameter	6" (MIX-4001) 4" (MIX-4002)
Height	0.625" Height

Ordering Information

Model	Description
MIX-4001	6" Detector Base
MIX-4002	4" Detector Base



Canada

25 Interchange Way Vaughan, ON L4K 5W3
Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.

4575 Witmer Industrial Estates Niagara Falls, NY 14305
Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.

CATALOG NUMBER **9505**

Rev. 1