

[TX3 Series]

VOICE ENTRY

TX3 Illuminated Directory Voice Access Systems

Simplifying Access Control

TX3 Illuminated Directory Voice Access Systems are ideal for resident and visitor access control for small buildings. They provide an easy to read illuminated directory for bulletins or signage, are very durable, and interface with other TX3 Platform solutions. You will also get free technical support and a 3 year warranty.

Universal Support – TX3 solutions integrate with CCTV, strobes and other devices. The LED illuminated directory and the 16 button keypad make for easy viewing at night

Durable Design – Unlike other products on the market, TX3 solutions are crafted out of stainless steel and are vandal resistant, surface mount models are perfect for outdoor applications. They also provide flexible mounting options – surface, flush or gooseneck

Flexible Communication – TX3 solutions connect directly to other panels and can be networked using RS-485 and/or TCP/IP for easy remote programming and maintenance. A variety of protocols enable the user to easily and remotely manage the panel(s) through USB, modem or TCP/IP





Features

- Add TX3-IP module for TCP/IP networking
- Multi-lingual Display and Voice Greeting (English, French-Canadian and Spanish) that provides instructions on how to use entry panel
- Concierge/Security Desk/Guard Phone capability
- Supports both AutoDialer (ADC/PSTN) and NSL (No phone bill)
- Dials up to 18 digit telephone numbers
- System can be configured locally using the keypad or a computer with the TX3 configuration software
- For remote programming use a modem and a TX3-MDM modem module installed in the lobby unit, or use the TX3-IP module for TCP/IP local/remote connectivity
- 5000 record event log
- Industry Canada and F.C.C. approved

Standard Options

- Postal lock provisions for letter carrier access
- Covert Camera CAM-3 to provide full facial capture
- Thermostat controlled heater TH-102 for exterior cold environments.
- TX3 Platform allows for standalone or network-wide connections & scalability

Applications

- Provides resident/visitor access control for small buildings such as condominiums, apartment buildings, office buildings, gated communities and industrial buildings with up to 200 occupants or users
- Universal enclosure supports surface, semi-flush or pedestal mounting options (Optional adapter plate required to mount to a standard gooseneck post Model: TX3-UGA)

Dimensions

TX3-120U-C

16 5/8" H x 10 1/8" W x 3" D

TX3-UFT Semi-Flush Trim Ring

16 1/4" H x 10 5/8" W x 2 3/4" D

(Dimensions are for wall cutout)

TX3-120C-C

16 7/8" H x 10 3/8" W x 3" D

(Dimensions are for wall cutout)

18 1/2" H x 12" W x 1/2" D

(Outside frame dimensions)

TX3-120C-C enclosure is flush mount only



TX3-120U-C
Surface Mount
Universal Enclosure

TX3-120C-C
Flush Mount
Continental Enclosure

LED Illuminated for easy viewing at night



For more information call
1.888.660.4655
or visit **Mircom.com**

The contents of this document may be changed by Mircom Technologies Ltd. without notice. Mircom makes no representations or warranties about the completeness or accuracy of these contents and expressly disclaims liability howsoever arising therefrom. These contents, including all referenced trade names, logos, graphics, marks and copy right information, registered or unregistered, are the exclusive property of Mircom and shall not, without its prior consent, be used, reproduced, stored or transmitted by any means. Purchase of Mircom products is subject to standard warranties, software license agreement and terms and conditions, available on request.

ISO 9001:2008
REGISTERED