















Photo	Mircom Part #	Specification
	HDD-4	Surveillance grade HDD (WD Purple or Seagate based on availability) 4TB 3.5" SATA3 HDD / 3-year warranty
	HDD-6	Surveillance grade HDD (WD Purple or Seagate based on availability) 6TB 3.5" SATA3 HDD / 3-year warranty
	HDD-8	Surveillance grade HDD (WD Purple or Seagate based on availability) 8TB 3.5" SATA3 HDD / 3-year warranty
	HDD-10	Surveillance grade HDD (WD Purple or Seagate based on availability) 10TB 3.5" SATA3 HDD / 3-year warranty
	MW-LC22	22-inch monitor, 1080p resolution,75Hz refresh rate Dimension (mm): 493.06(W) × 382.69(H) × 199.83(D) Input signal: HDMI and VGA Input Voltage DC 12V, 2A. Power consumption 24W
	MW-LC24	24-inch monitor, 1080p resolution,75Hz refresh rate Dimension (mm): 540.38(W) × 417.55(H) × 199.83(D) Input signal: HDMI and VGA Input Voltage DC 12V, 2A. Power consumption 24W
	MW-LC27	27-inch monitor, 1080p resolution,75Hz refresh rate Dimension (mm): 671(W) × 437(H) × 199(D) Input signal: HDMI and VGA Input Voltage DC 12V, 2A. Power consumption 24W
	PW-POE-P30	Support multiple Cam(up to 3) with ONE existing cable. No additional power required Extend 100M, PoE supply power 30W (IEEE802.3af/at), Operating temperature: -20 ° C to 55 ° C
	PW2020-6T2G-EX	BT 60W POE support; Wall mount or Pole mount bracket included, Total Power Budget : 96W 10BASE-T or 1000BASE-TX RJ45 port of Ethernet, IEEE 802.3af/at power over Ethernet, Operating Temperature: -20°C ~55°C (-14°~122°F) Dimensions(L×W×H) 310mm x 260mm x 100mm
	PW2020-8T-IN	PoE Watchdog AI Function The Max output power of the port is 60W, Total Power Budget : 96W 6 x 100 Mbps + 2 x 10/100/1000 Mbps PoE ports switch Networking standard: IEEE802.3af/at/bt power over Ethernet, Operating Temperature: -10°C ~50°C (-14°~122°F), AC 110 ~ 220V Total ≤120W Dimensions(L×W×H) 187mm*139mm*43mm
	PW2020-16T-2F-IN	PoE Watchdog AI Function The Max output power of the port is 60W, Total Power Budget : 240W 14 x 100 Mbps + 2 x 1000 Mbps PoE ports switch Networking standard: IEEE802.3af/at/bt power over Ethernet, Operating Temperature: -10°C ~50°C (-14°~122°F), AC 110 ~ 220V Total ≤300W Dimensions(L×W×H) 430mm x 180mm x 45mm

	PW2020-24T-2F-IN	PoE Watchdog AI Function The Max output power of the port is 60W, Total Power Budget : 240W 22 x 100 Mbps + 2 x 1000 Mbps PoE ports switch Networking standard: IEEE802.3af/at/bt Power over Ethernet, Operating Temperature: -20°C ~50°C (-14°~122°F), AC 110 ~ 220V Total ≤300W Dimensions(L×W×H) 430mm x 180mm x 45mm
	TR-WM03-D-IN	Wall Mount Bracket for dome cameras TR-WM03-D used for IPC31*, IPC32* , IPC361* & IPC360*, EC-D4F28M-V3 series Dimensions(L×W×H) 183mm x 127mm x 126mm Weight 0.52kg
	TR-UP06-C-IN	Pole mount (with adjustable pole straps) for TR-JB-07-IN or TR-WM-03/04 with TR-JB-07-IN Dimensions (L × W × H) 120mmx120mmx53.4mm (5"x5.35"x2.46") Weight 0.45kg
	TR-UC08-C	Corner mount for Bullet and Dome (works with TR-WM03-B, TR-WM03-D, TR-WM04, TR-JB05-A, TR-JB05-B, TR-JB07) Dimensions(L×W×H) 137mmx127mmx116mm Weight 0.42kg
	TR-CM24-IN	Dome Pendent Mounting Bracket (Fit with TR-JB03/JB04) Note: TR-JB03/JB04 shall order separately Dimensions (DxL)Φ110mmx223.5mm Weight 0.25kg
	TR-SE24-A-IN	"Dome Pendent Mounting Pole (520mm,need Pendent mount adaptor with TR-CM24-IN)" Dimensions (DxL) "Φ32mmx520mm Weight 0.16kg
	TR-JB03-G-IN	TR-JB03-G-IN for IPC31* IPC361* , IPC360* & IPC32* , EC-D4F28M-V3 series cam Dimensions(D×W) Φ109mm x 36mm Weight 0.16kg
	TR-JB03-I-IN	TR-JB03-I-IN for IPC362* series cam Dimensions(D×W) Φ117.8mm x 36mm Weight 0.2kg
	TR-JB08-IN	work with IPC3224 (camera) Dimensions(LxWxH) 108.3mm x 176mm x 48mm Weight : 0.24